



Características	
Modelo	LME-00212
Categoría	Muro Exterior Descubierta LED
Material	Al+AL
Terminado	PLATA
Pantalla	0
Indice de Protección [IP]	IP54
Base	N/A
Dimensiones mm	110*45 mm
Lúmenes	N/A
Temperatura	3000K
Parametros Eléctricos	
Tensión Nominal [V~]	100-240V~
Consumo de Potencia [W]	2W
Frecuencia Nominal [Hz]	50/60Hz
Consumo de Corriente [A]	0.02A
Temperatura de Operación	0 - 40 °C
Beneficios	
Garantía	2 Años de Garantía
Certificación	NOM



Product Information

Product Type: LME-00212
Product Spec: 1.8W

Product Number: 47

CIE Colorimetric Parameters

Chromaticity coordinates: $x=0.4345$ $y=0.3990$ $u(u')=0.2512$ $v=0.3460$ $v'=0.5190$
 CCT: $T_c=3000K$ ($duv=-0.00169$) Color Ratio: $R=0.229$ $G=0.747$ $B=0.024$
 Peak Wavelength: 648.1nm Half Bandwidth: 2.5nm
 Dominant Wavelength: 583.4nm Color Purity: 0.502
 CRI: $R_a=82.3$, $avgR(1\sim14)=76.8$, $avgR(1\sim15)=76.6$ TM30: $R_f=81$, $R_g=98$
 $R_1=81$ $R_2=90$ $R_3=96$ $R_4=81$ $R_5=81$ $R_6=88$ $R_7=82$ $R_8=59$
 $R_9=7$ $R_{10}=77$ $R_{11}=80$ $R_{12}=72$ $R_{13}=83$ $R_{14}=98$ $R_{15}=74$
 Color Quality Scale: $Q_a=81.4$, $Q_f=82.4$, $Q_p=84.2$, $Q_g=93.4$
 $Q_1=77$ $Q_2=96$ $Q_3=81$ $Q_4=79$ $Q_5=83$ $Q_6=82$ $Q_7=82$ $Q_8=85$
 $Q_9=96$ $Q_{10}=88$ $Q_{11}=84$ $Q_{12}=82$ $Q_{13}=82$ $Q_{14}=72$ $Q_{15}=73$



Photometric Parameters

Luminous Flux: 61.16 lm Efficiency: 48.16 lm/W Radiant Power: 0.193 W
 EEI: 0.13 Energy Efficiency Class: A+ (EU 874-2012)
 Pupil Flux: 76.44 Plm Pupil Lumens Per Watt: 60.19 Plm/W Pupil Factor (Kp): 1.250

Electric Parameters

Voltage: 127.30V Current: 0.0210A Power: 1.27W
 Power Factor: 0.4800 Frequency: 60.00Hz

Test Information

Scan Range: 380~800:1nm Photometric Method: sphere-spectroradiometer
 Stabilization Time: 0 Min Photometric Condition: Sphere diameter: 1.50m, 4PI
 Max of Signal: 13432 (5540) CCD Integration Time: 10000.00 ms